WHATCOM FERTILIZER SPREADERS



Narrow Profile Berry Model

WHATCOM MANUFACTURING'S Stainless Steel Fertilizer Spreaders are specifically designed for the BERRY grower. Extra narrow width and higher capacity will accommodate mature fields and minimize time and trips required to cover larger acreage plantings. Our twin belt discharge evenly spreads fertilizer on two rows simultaneously. This feature in conjunction with the ground driven floor chain provides for concise application rates regardless of ground speed.





405 Birch Bay-Lynden Road
LYNDEN, WA 98264
Phone: **360-354-3094**
Fax: **360-354-5434**
Web Page: ***www.whatcommfg.com***
E-Mail: ***info@whatcommfg.com***

Whatcom **M**anufacturing **F**ertilizer **S**preader **S**pecifications
MODELS 250-NP and 300-NP

- Narrow Profile **250** Fertilizer Spreader
- Dimensions:
  58” Outside Tire Width
  42” Hopper Width
  81” Overall Height
  60” Hopper Length
  114.5” Overall Length
- Single Axle with 12.5L-16 Flotation Tires
- 55.75 Cubic Foot Capacity Stainless Steel Hopper
- Stainless Steel Floor Chain
- Side Banding Twin Belt Discharge with Hydraulic Motor Drives
- Stainless Steel Top Lid
- Adjustable Flow Rate of 80 to 700 Pounds per Acre



- Narrow Profile **300** Fertilizer Spreader
- Dimensions:
  60” Outside Tire Width
  42” Hopper Width
  89” Overall Height
  96” Hopper Length
  151” Overall Length
- Tandem Axle Spring Suspension with 31x15.5 Flotation Tires
- 91 Cubic Foot Capacity Stainless Steel Hopper
- Stainless Steel Floor Chain
- Side Banding Twin Belt Discharge with Hydraulic Motor Drives
- Stainless Steel Top Lid
- Adjustable Flow Rate of 80 to 700 Pounds per Acre



Whatcom Manufacturing will be happy to answer any questions regarding this Narrow Profile Fertilizer Spreader. Give us a call at **(360)-354-3094**, or email your questions to ***info@whatcommfg.com***.